

## Standpipe Piezometers

### Model 601

The Solinst Model 601 Standpipe Piezometer is designed to be placed within a drilled hole to provide a filtered inlet point. The pointed PVC tip is also suitable for pushing into very loose sands at the base of a borehole, a stream, or into very loose tailings pond sediments.

The 601 Standpipe Piezometer is excellent for metals sampling, as it is composed of a preformed Vyon tube set inside a perforated PVC piezometer tip. The Model 601 is also well suited for water level monitoring, permeability measurements, air sparging, construction control, de-watering drainage operations, and slope stability investigations, etc.

The 601 Standpipe Piezometer connects to the surface with 3/4" Sch. 40 PVC (0.804" ID x 1.050" OD) plain end extensions, using slip couplings. Reducer couplings can also be used to connect to other sizes of riser pipe or casing. The standard 601 Standpipe Piezometer lengths available are: 6", 1ft, 2ft and 3ft (15cm, 30cm, 60cm and 90cm).

Solinst also offers the Model 615 stainless steel Drive-Point Piezometer, which is designed to be driven directly into the ground using a slide hammer. (See Model 615 Drive-Point Piezometer Data Sheet for more information.)




## Filter Specifications

- Porous HDPE (Vyon)
- Average pore size 60 microns
- Keeps out silts and fine sands

## Model 601

### Standpipe Piezometer



## Applications

- Water level monitoring
- Permeability measurements
- Construction control
- De-watering and drainage operations
- Slope stability investigations
- Air Sparging: a 1 ft. Piezometer has 18 x 3/8" diameter holes i.e. 2 sq inches
- Metals Sampling

## Advantages

- Reliable
- Low cost
- 60 micron filter element
- Rigid PVC housing protects Vyon filter installation

®Solinst is a registered trademark of Solinst Canada Ltd.

Printed in Canada  
June 6, 2013

**For further information contact: Solinst Canada Ltd.**  
 Fax: +1 (905) 873-1992; (800) 516-9081 Tel: +1 (905) 873-2255; (800) 661-2023  
 35 Todd Road, Georgetown, Ontario Canada L7G 4R8  
 Web Site: [www.solinst.com](http://www.solinst.com) E-mail: [instruments@solinst.com](mailto:instruments@solinst.com)

# Solinst®